

AC(5) 130/160/180/200 STICK[SMAW]

PRODUCT DESCRIPTION

Single phase, AC output
 Portable, fan cooled
 Stepless current setting
 Power indicator
 Thermal protection



50/60
Hz



AC

1
PHASE



■ TECHNICAL PARAMETER

Model AC(5)130AC(5)160AC(5)180AC(5)200AC(5)130DUALAC(5)160DUALAC(5)180DUALAC(5)200DUAL

Input Power (V)	230	230	230	230	230/400	230/400	230/400	230/400
Rated Input Current (A)	27	34	38	45	27/16	34/20	38/22	43/25
Rated Input Capacity (kVA)	6.3	7.9	8.8	10	6.3	7.9	8.8	10
Rated Open Circuit Voltage(V)	48	50	50	50	48	50	50	50
Welding Current Adjustment Range(A)	40-115	45-140	55-160	60-180	45-115	45-140	55-160	60-180
Rated Output(A)	10%@115	10%@140	10%@160	10%@180	10%@115	10%@140	10%@160	10%@180

(20°C) / (40°C)	10 % @ 115	10 % @ 140	10 % @ 160	10 % @ 180	10 % @ 115	10 % @ 140	10 % @ 160	10 % @ 180
Weight (kg)	17	18	22	23	17	18	22	23
Electrode Diameter (mm)	1.6-3.2	1.6-4.0	1.6-4.0	1.6-4.0	1.6-3.2	1.6-4.0	1.6-4.0	1.6-4.0
LxWxH (mm)	500x230x345	500x230x345	500x230x345	500x230x345	505x275x325	505x275x325	505x275x325	505x275x325

■ PARTS

ACCESSORIES



OPTIONAL

