

DELTAPOWER STICK[SMAW]



PRODUCT DESCRIPTION

Three phase thyristor DC welder
 On wheel, fan cooled
 Power indicator
 Thermal protection
 Stepless current setting
 Digital display
 Adjustment arc force
 Remote control
 Available for gouging when amp more than 500amp
 Suitable for rutile, basic and cellulosic electrode



■ TECHNICAL PARAMETER

Model	DELTAPOWER 315E(A)	DELTAPOWER 400E(A)	DELTAPOWER 500E(A)	DELTAPOWER 630E(A)
Input Power (V)	400	400	400	400
Rated Input Current (A)	38	52	65	85
Rated Input Capacity (kVA)	25	34	42	56
Rated Open Circuit Voltage(V)	68	70	72	75
Welding Current Adjustment Range(A)	40-315	50-400	60-500	120-630
Rated Output(A) (20°C) / (40°C)	60%@315	60%@400	60%@500	60%@630
Weight (kg)	180	195	200	235
Electrode Diameter (mm)	1.6-4.0	2.5-5.0	2.5-6.0	3.2-8.0
LxWxH (mm)	1100x700x830	1100x700x830	1010x700x830	1010x700x830

■ PARTS

ACCESSORIES



OPTIONAL

