

ESTICK STICK[SMAW]

PRODUCT DESCRIPTION

- Portable stick welder
- Advanced IGBT technology
- Voltage compensation
- Thermal protection
- Stepless current setting
- Hot start, anti-sticking, arc force
- Available for rutile and basic electrode
- Continuous welding
- Lift Arc TIG as options



■ DETAIL DISPLAY



Standard Version

E Version

■ TECHNICAL PARAMETER

Model	ESTICK 140 E	ESTICK 160 (E)	ESTICK 180 (E)	ESTICK 200 (E)
Input Power (V)	230	230	230	230
Rated Input Current (A)	27	31	34	39
Rated Input Capacity (kVA)	6.2	7.1	7.8	9

Rated Open Circuit Voltage(V)	66	66	69	69
Welding Current Adjustment Range(A)	20-140	20-160	20-180	20-200
Rated Output(A) (20°C) / (40°C)	40%/20%@140	40%/20%@160	35%/20%@180	30%/15%@200
Weight (kg)	4.6	4.6	4.75	4.75
Electrode Diameter (mm)	1.6-3.2	1.6-4.0	1.6-4.0	1.6-5.0
LxWxH (mm)	385x125x260	385x125x260	394x154x293	394x154x293

PARTS

ACCESSORIES



OPTIONAL

